(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 17 November 2005 (17.11.2005)

PCT

(10) International Publication Number WO 2005/109478 A1

(51) International Patent Classification⁷: H01L 21/205, C23C 16/34

(21) International Application Number:

PCT/JP2005/009008

(22) International Filing Date: 11 May 2005 (11.05.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2004-142657 60/572,269

12 May 2004 (12.05.2004) JP 19 May 2004 (19.05.2004) US

(71) Applicant (for all designated States except US): SHOWA DENKO K.K. [JP/JP]; 13-9, Shibadaimon 1-chome, Minato-ku, Tokyo, 1058518 (JP).


- (72) Inventors; and
- (75) Inventors/Applicants (for US only): MIKI, Hisayuki [JP/JP]; c/o Showa Denko K.K. 5-1, Yawata Kaigan dori,

Ichihara-shi, Chiba 2900067 (JP). TAKEDA, Hitoshi [JP/JP]; c/o Showa Denko K.K. 5-1, Yawata Kaigan dori, Ichihara-shi, Chiba 2900067 (JP).

- (74) Agents: AOKI, Atsushi et al.; A. Aoki, Ishida & Associates, Toranomon 37 Mori Bldg., 5-1, Toranomon 3-chome, Minato-ku, Tokyo, 1058423 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: P-TYPE GROUP III NITRIDE SEMICONDUCTOR AND PRODUCTION METHOD THEREOF



(57) Abstract: An object of the present invention is to provide a method for producing a p-type Group III nitride semiconductor which can be used to produce a light-emitting device exhibiting a low operation voltage and a sufficiently high reverse voltage. The inventive method for producing a p-type Group III nitride semiconductor comprises, during lowering temperature after completion of growth of a Group III nitride semiconductor containing a p-type dopant, immediately after completion of the growth, starting, at a temperature at which the growth has been completed, supply of a carrier gas composed of an inert gas and reduction of the flow rate of a nitrogen source; and stopping supply of the nitrogen source at a time in the course of lowering the temperature.

GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report

 before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.